

Data sheet

IM 253DP, PROFIBUS-DP slave (253-1DP31)

Technical data

Order no.	253-1DP31
------------------	------------------

Type	IM 253DP, PROFIBUS-DP slave
------	-----------------------------

General information

Note	-
Features	DC 24 V 12 Mbit/s Configuration via GSD file of VIPA Up to 8 peripheral modules 244 Byte input- and 244 Byte output data

Technical data power supply

Power supply (rated value)	DC 24 V
Power supply (permitted range)	DC 20.4...28.8 V
Reverse polarity protection	yes
Current consumption (no-load operation)	50 mA
Current consumption (rated value)	300 mA
Inrush current	60 A
$I_{\Delta t}$	0.4 A ² s
Max. current drain at backplane bus	0.8 A
Max. current drain load supply	-
Power loss	1.5 W

Status information, alarms, diagnostics

Status display	yes
Interrupts	yes, parameterizable
Process alarm	yes, parameterizable
Diagnostic interrupt	yes, parameterizable
Diagnostic functions	yes, parameterizable
Diagnostics information read-out	possible
Supply voltage display	green LED
Service Indicator	-
Group error display	red SF LED
Channel error display	none

Hardware configuration

Racks, max.	1
Modules per rack, max.	8
Number of digital modules, max.	8
Number of analog modules, max.	8

Communication

Fieldbus	PROFIBUS-DP to EN 50170
Type of interface	RS485
Connector	Sub-D, 9-pin, female
Topology	Linear bus with bus termination at both ends
Electrically isolated	yes
Number of participants, max.	125
Node addresses	1 - 125

Transmission speed, min.	9.6 kbit/s
Transmission speed, max.	12 Mbit/s
Address range inputs, max.	244 Byte
Address range outputs, max.	244 Byte
Number of TxPDOs, max.	-
Number of RxPDOs, max.	-

Housing

Material	PPE / PA 6.6
Mounting	Profile rail 35 mm

Mechanical data

Dimensions (WxHxD)	25.4 mm x 76 mm x 78 mm
Net weight	90 g
Weight including accessories	-
Gross weight	-

Environmental conditions

Operating temperature	0 °C to 60 °C
Storage temperature	-25 °C to 70 °C

Certifications

UL certification	yes
KC certification	-